

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan


“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 482 (1981): Reels for Covered Round Electrical Winding Wires [ETD 33: Winding Wire]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



Indian Standard

SPECIFICATION FOR
REELS FOR COVERED ROUND
ELECTRICAL WINDING WIRES

(Third Revision)

Second Reprint NOVEMBER 1998

UDC 621.3.046 : 621.315.3 : 621.3.045

© Copyright 1981

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

SPECIFICATION FOR REELS FOR COVERED ROUND ELECTRICAL WINDING WIRES (Third Revision)

Winding Wires Sectional Committee, ETDC 33

Chairman

SHRI K. DORAISWAMY
Building 2, Five Star Apartments,
Bund Garden Road, Pune

Members

SHRI S. B. BAPAT
SHRI N. S. SHETH (*Alternate*)
SHRI J. S. BHAN

SHRI S. N. SENGUPTA (*Alternate*)
SHRI J. L. CHHABRA

SHRI J. S. PASSI (*Alternate*)
DR O. P. CHHABRA
SHRI B. RAMAN (*Alternate I*)
SHRI S. AMEERJAN (*Alternate II*)

SHRI K. DAS GUPTA
SHRI GOPAL NARAIAAN (*Alternate*)
SHRI S. G. DESHMUKH
SHRI A. R. SALVI (*Alternate*)
MAJOR S. B. DESHPANDE

SHRI P. N. LABRU (*Alternate*)

SHRI P. GHOSH
SHRI T. CHOUDHURY (*Alternate*)

SHRI V. GOPALAKRISHNAN
SHRI J. NAGESH BHATT (*Alternate*)

SHRI D. P. GUPTA
Directorate General of Technical Development,
New Delhi

SHRI P. N. HIRIYANNAIAH
Kirkoskar Electric Co Ltd, Bangalore
JOINT DIRECTOR TRACTION
Research Designs and Standards Organization,
Lucknow

INSTALLATION—II

DEPUTY DIRECTOR STANDARDS

(ELECTRICAL) B-3 (*Alternate*)

Representing

Dr Beck & Co (India) Ltd, Pune

The National Insulated Cable Co of India Ltd,
Calcutta

Directorate General of Supplies and Disposals
(Inspection Wing), New Delhi

Bharat Heavy Electricals Ltd, Bhopal

Indo-American Electricals Ltd, Calcutta

Bharat Bijlee Ltd, Bombay

Raksha Mantralaya, Manakikaran Nideshalaya,
New Delhi

Indian Cable Co Ltd, Calcutta

Indian Telephone Industries Ltd, Bangalore

Directorate General of Technical Development,
New Delhi

Kirkoskar Electric Co Ltd, Bangalore
Research Designs and Standards Organization,
Lucknow

(Continued on page 2)

© Copyright 1981

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

<i>Members</i>	<i>Representing</i>
SHRI A. H. KULKARNI	Wandleside National Conductors Ltd, Pune
SHRI V. M. JOSHI (<i>Alternate</i>)	
SHRI D. D. MEHTA	Shakti Insulated Wires Pvt Ltd, Bombay
SHRI S. NAGARAJAN (<i>Alternate</i>)	
SHRI B. MUKHOPADHYAY	National Test House, Calcutta
SHRI SANATH KUMAR (<i>Alternate</i>)	
SHRI P. F. PARIKH	Winding Wires Manufacturers' Association of India, Bombay
PROF N. SEN (<i>Alternate</i>)	
DR G. M. PHADKE	Indian Electrical Manufacturers' Association, Bombay
SHRI D. B. GUPTA (<i>Alternate</i>)	
SHRI P. L. PRADHAN	Jyoti Ltd, Vadodara
SHRI B. G. SHARMA (<i>Alternate</i>)	
SHRI A. K. RAMAN	Asian Cables Corporation Ltd, Bombay
SHRI N. P. SANGAMESWARAN	Devidayal Electronics and Wires Ltd, Bombay
SHRI P. S. LAMBA (<i>Alternate</i>)	
SHRI Y. K. SHAH	Peico Electronics & Electricals Ltd, Bombay
SHRI A. M. GHATAK (<i>Alternate</i>)	
SHRI R. SOMASEKHARA	Bharat Electronics Ltd, Bangalore
SHRI S. V. KABADE (<i>Alternate</i>)	
SHRI A. N. SRIVATHSA	NGEF Ltd, Bangalore
SHRI JAGANNATHA RAO (<i>Alternate</i>)	
SHRI S. P. SACHDEV,	Director General, BIS (<i>Ex-officio Member</i>)
Director (Elec tech)	

Secretary

SHRI R. G. KALE

Deputy Director (Elec tech), BIS

Indian Standard
**SPECIFICATION FOR
 REELS FOR COVERED ROUND
 ELECTRICAL WINDING WIRES**
(Third Revision)

0. FOREWORD

0.1 This Indian Standard (Third Revision) was adopted by the Indian Standards Institution on 15 May 1981, after the draft finalized by the Winding Wires Sectional Committee had been approved by the Electrotechnical Division Council.

0.2 This standard was first published in 1953 with the object of reducing the wide range of sizes of reels for covered electrical winding wires.

0.2.1 The first revision was issued in 1962 with a view to giving all the quantities and dimensions in metric system, to incorporate the metric wire sizes in accordance with IS: 1594-1960* which was subsequently withdrawn.

0.2.2 The second revision was issued in 1968 to include moulded plastic reels in the standard and to unify the reference numbers and the important dimensions of the wooden reels and moulded plastic reels to achieve interchangeability.

0.2.3 In this third revision wooden reels of sizes below 160 mm have been withdrawn so that plastic reels which are easy to handle due to lighter weight could be introduced and moulded plastic reels of sizes 315 and 400 mm have been deleted. The flange sizes are taken from R10 series of preferred numbers and they satisfy to a large extent the present practice of flange sizes.

0.3 The design aspects have been given careful consideration in deciding the various dimensions of the reels. One important aspect is that the ratio between the flange and barrel diameter has been kept near about 1.6 : 1 with the object of lessening the variation in the tension and also to facilitate easy unwinding of the wires.

0.4 This standard contains clause 5.1 which calls for agreement between the purchaser and the supplier or permit the purchaser to use his option for selection to suit his requirements.

*Specification for metric sizes of copper wires and conductors for electrical purposes.

0.5 In preparing this standard, assistance has been derived from the following:

BS 1489:1972 Specification for the packaging of covered winding wires for electrical purposes, issued by the British Standards Institution.

DIN 46399-1959 Delivery spools for bare and insulated wires; dimensions issued by Deutscher Normenausschuss.

0.6 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated expressing the result of a test, shall be rounded off in accordance with IS : 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard specifies the requirements regarding materials, construction, dimensions, tolerances, eccentricity and sizes for reels for covered round wires for winding electrical machinery and apparatus.

2. MATERIALS AND CONSTRUCTION

2.1 The materials used in the construction of the reels shall have the required mechanical strength so that the reels do not warp in actual use or in storage. The material shall have no deleterious effect on the fibres, enamel or other coverings of the wires.

2.2 The flanges and the barrel shall be smooth and free from protruding material capable of damaging the wire or the hands of the winding operator during rotation of the reel. Bolts, screws, nails, etc, if used in the construction of the reel shall be countersunk, so that the heads are below the surface of the flange.

2.3 Wooden reel having a flange diameter of 160 mm shall be varnished and flanges of all wooden reels shall be smoothened.

2.3.1 All wooden components shall be manufactured of seasoned wood preferably softwood. The wood used in the construction shall be sound and free from defects that materially weaken the component parts of the reels. If required by the purchaser, a wood preservative which shall have no deleterious effects on fibres or enamel coverings of wires, be applied to the entire reel.

2.4 Parts of reels made from ferrous metals shall be treated with rust preventive finish or coating to minimize rusting during transit and storage.

*Rules for rounding off numerical values (*revised*).

2.5 All reels shall be provided with recess of adequate depth to accommodate the label.

2.6 In case of plastic reels, the plastic material and reel flanges design (by providing necessary ribs, etc) has to be such that the reel should be able to withstand a breaking stress of minimum 6 MN/m^2 when pulled slowly at a rate of approximately 300 mm/minute after clamping the flanges properly.

2.7 No portion of the plastic reel shall warp when kept in an air-oven at 70°C for one hour.

2.8 The colour of the plastic reel shall be sufficiently stable.

3. DIMENSIONS AND TOLERANCES

3.1 Reel sizes shall always be denoted by the reference numbers shown in Table 1 or 2.

NOTE — Each reference number shall be given as the diameter of flange in millimetres.

3.2 The dimensions and tolerances of the reel shall be in accordance with Table 1 and 2.

3.3 The inner and outer edges of reel flanges shall be rounded to a radius of not less than 1.0 mm for reels up to and including 160 mm in diameter, and not less than 1.5 mm for reels above 160 mm in diameter so as to avoid burrs and sharp corners.

3.4 The bore of the reel shall be coned to an included angle of 60° and shall be as shown in the dimensional drawing.

4. ECCENTRICITY AND FLANGE RUN-OUT

4.1 The unbalance and axial throw of the flanges shall be negligible.

4.2 The eccentricity of the reels when measured in the manner described in Appendix A, shall be not more than the values given in col 20 of Table 1 and col 18 of Table 2.


4.3 The run-out of the inside faces of each flange of reels of 160 mm diameter and smaller, as shown by an indicator gauge, shall nowhere exceed the total tolerance on traverse given in col 6 of Tables 1 and 2.

5. SIZES OF WIRES ON REELS

5.1 In order to meet the varying requirements choice of reel is provided. The purchaser shall state the size of the reel required when ordering the wire.

TABLE 1 SIZES AND TOLERANCES OF WOODEN REELS

(Clauses 3.1, 3.2, 4.2, 4.3 and 6.1)




All dimensions in millimetres.

Ref No.	Flange, A		Max Overall length <i>L</i>	Traverse, B		Barrel, D		Bore, E		Cone, F		Peg Hole, G		Peg Hole, R		Radius of Rim, <i>r</i>	Label Recess, H		Eccentricity <i>e</i>
	Dia	Tolerance		Length	Tolerance	Dia	Tolerance	Dia	Tolerance	Major Dia	Tolerance	Dia	Tolerance	Radius	Tolerance		Dia	Tolerance	
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)
160	160	-3.0 +0.0	160	128	+1.0 -0.0	100	±2.0	22	+2.0 -0.0	34	+2.0 -0.0	13	+0.5 -0.0	32	±1.0	4	105	±2.0	1.55
200	200	-3.0 +0.0	200	160	+1.0 -0.0	125	±2.0	22	+2.0 -0.0	34	+2.0 -0.0	13	+0.5 -0.0	32	+1.0 -0.0	4	105	±2.0	2.0
250	250	-3.0 +0.0	200	160	+2.0 -0.0	160	±3.0	36	+2.0 -0.0	48	+2.0 -0.0	13	+0.5 -0.0	32	+1.0 -0.0	4	105	±2.0	2.5
315	315	-3.0 +0.0	200	160	+2.0 -0.0	200	±3.0	36	+2.0 -0.0	48	+2.0 -0.0	13	+0.5 -0.0	32	+1.0 -0.0	4	105	±2.0	3.0
400	400	-3.0 +0.0	200	160	+2.0 -0.0	200	±3.0	36	+2.0 -0.0	48	+2.0 -0.0	13	+0.5 -0.0	32	+1.0 -0.0	4	105	±2.0	4.0

TABLE 2 SIZES AND TOLERANCES OF MOULDED PLASTIC REELS

(Clauses 3.1, 3.2, 4.2, 4.3 and 6.1)



Ref No.	Flange, A		Max. overall Length L	Traverse, B		Barrel, D		Bore, E		Cone, F		Peg Hole, G		Peg Hole, R		Radius of Rim r	Eccentricity e	Weight of Reel in gm
	Dia	Tolerance		Length	Tolerance	Dia	Tolerance	Dia	Tolerance	Major Dia	Tolerance	Dia	Tolerance	Radius	Tolerance			
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)
50	50	+1.5 -0.0	50	38	+0.20 -0.00	32	±0.15	11	+0.1 -0.0	15	+1.0 -0.0	-	-	-	-	1.0	0.25	22
63	63	+1.5 -0.0	63	49	+0.20 -0.00	40	±0.15	11	+0.1 -0.0	15	+1.0 -0.0	-	-	-	-	1.5	0.25	40
80	80	+1.5 -0.0	80	64	+0.20 -0.00	50	±0.15	16	+0.2 -0.0	24	+1.0 -0.0	7	+0.25 -0.00	20	±0.5	2.0	0.25	70
100	100	+1.5 -0.0	100	80	+0.20 -0.00	63	±0.15	16	+0.2 -0.0	24	+1.0 -0.0	7	+0.25 -0.00	20	±0.5	3.0	0.25	125
120	125	+1.5 -0.0	125	100	+0.20 -0.00	80	±1.5	16	+0.2 -0.0	24	+1 -0	7	+0.25 -0.00	20	±0.5	3.0	0.35	200
160	160	+1.5 -0.0	160	128	+0.20 -0.00	100	±1.5	22	+0.2 -0.0	34	+1 -0	13	+0.50 -0.00	32	±0.5	3.0	0.45	350
200	200	+2.0 -0.0	200	160	+0.20 -0.00	125	±1.5	22	+0.2 -0.0	34	+1 -0	13	+0.50 -0.00	32	±0.5	4.0	0.75	600
250	250	+3.0 -0.0	200	160	+0.20 -0.00	160	±2.0	36	+0.5 -0.2	49	+1 -0	13	+0.50 -0.00	32	±0.5	5.0	1.00	1 050

NOTE—The weights given under column 19 are for 'Polystyrene' bobbins, only as an approximate guide to manufactures. For bobbins other than 'Polystyrene', the weights specified will change according to the specific gravity of the plastic material used for making.

6. MARKING

6.1 The reference number given in col 1 of Table 1 or 2 shall appear either on the flange or on the barrel of each reel.

6.1.1 The reels may also be marked with the Standard Mark.

NOTE — The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

APPENDIX A

(Clause 4.2)

MEASUREMENT OF ECCENTRICITY AND FLANGE RUN-OUT

A-1. REELS OF 160 mm DIAMETER AND SMALLER

A-1.1 The reels shall be placed horizontally between centres of 60° included angle on a 16 mm diameter shaft (*see* Fig. 1), and shall be rotated slowly. The eccentricity shall be measured by a suitable indicator dial gauge *A*, placed in contact with the external surface of the barrel. The eccentricity of the reel is equivalent to half the measurement shown by the gauge. The run-out of the inside faces of the flange is shown by the appropriate indicator gauge *B*.

A-2. REELS OF 200 mm DIAMETER AND LARGER

A-2.1 The reels shall be placed on a horizontal 35 mm spindle, and shall be rotated slowly (*see* Fig. 2). The eccentricity shall be measured by a suitable indicator dial gauge *C* in contact with the external surface of the barrel. The eccentricity of the reel is equivalent to half the measurement shown by the gauge.




FIG. 1 MEASUREMENT OF ECCENTRICITY AND FLANGE RUN-OUT ON REELS 160 mm DIA AND SMALLER




FIG. 2 MEASUREMENT OF ECCENTRICITY REELS 200 mm DIA AND LARGER

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 323 0131, 323 3375, 323 9402

Fax: 91 11 3234062, 91 11 3239399, 91 11 3239382

Telegrams : Manaksanstha

(Common to all Offices)

Telephone

Central Laboratory:

Plot No. 20/9, Site IV, Sahibabad Industrial Area, Sahibabad 201010

8-77 00 32

Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002 323 76 17

*Eastern : 1/14 CIT Scheme VII M, V.I.P. Road, Maniktola, CALCUTTA 700054 337 86 62

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022 60 38 43

Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600113 235 23 15

†Western : Manakalaya, E9, Behind Marol Telephone Exchange, Andheri (East), MUMBAI 400093 832 92 95

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001 550 13 48

‡Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road, BANGALORE 560058 839 49 55

Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. Nagar, BHOPAL 462003 55 40 21

Plot No. 62-63, Unit VI, Ganga Nagar, BHUBANESHWAR 751001 40 36 27

Kalaikathir Buildings, 670 Avinashi Road, COIMBATORE 641037 21 01 41

Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001 8-28 88 01

Savitri Complex, 116 G.T. Road, GHAZIABAD 201001 8-71 19 96

53/5 Ward No.29, R.G. Barua Road, 5th By-lane, GUWAHATI 781003 54 11 37

5-8-56C, L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001 20 10 83

E-52, Chitaranjan Marg, C- Scheme, JAIPUR 302001 37 29 25

117/418 B, Sarvodaya Nagar, KANPUR 208005 21 68 76

Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, LUCKNOW 226001 23 89 23

NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010 52 51 71

Patliputra Industrial Estate, PATNA 800013 26 23 05

Institution of Engineers (India) Building 1332 Shivaji Nagar, PUNE 411005 32 36 35

T.C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPURAM 695034 6 21 17

*Sales Office is at 5 Chowringhee Approach, P.O. Princep Street, CALCUTTA 700072 27 10 85

†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007 309 65 28

‡Sales Office is at 'F' Block, Unity Building, Narashimaraja Square, BANGALORE 560002 222 39 71

Reprography Unit, BIS, New Delhi, India